



CONTACTOR, SIZE 6, 3-POLE AC-3, 55KW,
400/380V AUXILIARY CONTACTS 22 (2NO+2NC) DC
SOLENOID SYSTEM DC 24V

General details:

Size of the contactor		6
Protection class IP / on the front		IP00
Ambient temperature during operating	°C	-25 ... +55
Item designation - according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 - according to DIN EN 61346-2		K Q
Number of poles / for main current circuit		3
Operating current / at AC-1 / at 400 V - at 40 °C ambient temperature / rated value - at 60 °C ambient temperature / rated value	A	170 160
Impulse voltage resistance / rated value	kV	8

Main circuit:

Number of NC contacts / for main contacts		0
Number of NO contacts / for main contacts		3
Operational current / at AC-3 / at 400 V / rated value	A	110
Service power at AC-3 / at 400 V / rated value	kW	55

• at AC-1 / at 400 V / rated value

kW 105

Control circuit:

Design of activation / of the operating mechanism

conventional

Type of voltage / of the controlled supply voltage

DC

Control supply voltage

• for DC / rated value

V 24

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts

• lagging switching

0

• instantaneous switching

2

Number of NO contacts / for auxiliary contacts

• leading switching

0

• instantaneous switching

2

Connection type:

Design of the electrical connection

• for main current circuit

screw-type terminals

• for auxiliary and control current circuit

screw-type terminals

Identification number and letter for switching elements

22

Mechanical design:

Type of mounting

screw fixing

Type of fixing/fixation / series installation

Yes

Width

mm 120

Height

mm 150

Depth

mm 198

Certificates/approvals:

General Product Approval

**Declaration of
Conformity**

Test Certificates



CCC



GOST



UL



EG-Konf.

[Special Test
Certificate](#)

other

[Declaration of
Conformity](#)

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TB5017-0BB4/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TB5017-0BB4

last change:

Jan 28, 2013