OptiMOS®2 Power-Transistor


Features

- Fast switching MOSFET for SMPS
- Optimized technology for notebook DC/DC
- Qualified according to JEDEC[1] for target applications
- N-channel
- Logic level
- Excellent gate charge x $R_{DS(on)}$ product (FOM)
- Very low on-resistance $R_{DS(on)}$
- Avalanche rated
- dv/dt rated
- Pb-free lead plating; RoHS compliant


Product Summary

V_{DS}	30	V
$R_{DS(on),max}$	30	mΩ
I_D	7.2	A

PG-DSO-8



Type	Package	Marking
BSO300N03S	PG-DSO-8	300N3S



Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value		Unit
			10 secs	steady state	
Continuous drain current	I_D	T_A=25 °C[2]	7.2	5.7	A
		T_A=70 °C[2]	5.8	4.6	
Pulsed drain current	$I_{D,pulse}$	T_A=25 °C[3]	29		
Avalanche energy, single pulse	E_{AS}	I_D=7.2 A, R_{GS}=25 Ω	10		mJ
Reverse diode dv/dt	dv/dt	I_D=7.2 A, V_{DS}=20 V, di/dt=200 A/µs, $T_{j,max}$=150 °C	6		kV/µs
Gate source voltage	V_{GS}		±20		V
Power dissipation	P_{tot}	T_A=25 °C[2]	2.5	1.56	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150		°C
IEC climatic category; DIN IEC 68-1			55/150/56		

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - soldering point	R_{thJS}		-	-	35	K/W
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint, t_p≤10 s	-	-	110	
		minimal footprint, steady state	-	-	150	
		6 cm^2 cooling area[2], t_p≤10 s	-	-	50	
		6 cm^2 cooling area[2], steady state	-	-	80	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=8 µA	1.2	1.6	2	
Zero gate voltage drain current	I_{DSS}	V_{DS}=30 V, V_{GS}=0 V, T_j=25 °C	-	0.1	1	µA
		V_{DS}=30 V, V_{GS}=0 V, T_j=125 °C	-	10	100	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5 V, I_D=6.1 A	-	36	45	mΩ
		V_{GS}=10 V, I_D=7.2 A	-	25	30	
Gate resistance	R_G		-	0.6	-	Ω
Transconductance	g_{fs}	|V_{DS}|>2|I_D|$R_{DS(on)max}$, I_D=7.2 A	7	14	-	S

[1] J-STD20 and JESD22

[2] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm^2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.


[3] See figure 3

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=15 V, f=1 MHz	-	450	600	pF
Output capacitance	C_{oss}		-	160	210	
Reverse transfer capacitance	C_{rss}		-	23	34	
Turn-on delay time	$t_{d(on)}$	V_{DD}=15 V, V_{GS}=10 V, I_D=3.6 A, R_G=2.7 Ω	-	2.3	3.4	ns
Rise time	t_r		-	2.2	3.3	
Turn-off delay time	$t_{d(off)}$		-	9.3	14	
Fall time	t_f		-	1.6	2.4	
Gate Charge Characteristics[4)]						
Gate to source charge	Q_{gs}	V_{DD}=15 V, I_D=3.6 A, V_{GS}=0 to 5 V	-	1.3	1.8	nC
Gate charge at threshold	$Q_{g(th)}$		-	0.7	0.95	
Gate to drain charge	Q_{gd}		-	0.9	1.3	
Switching charge	Q_{sw}		-	1.5	2.2	
Gate charge total	Q_g		-	3.5	4.6	
Gate plateau voltage	$V_{plateau}$		-	3.0	-	V
Gate charge total, sync. FET	$Q_{g(sync)}$	V_{DS}=0.1 V, V_{GS}=0 to 5 V	-	3.1	4.1	nC
Output charge	Q_{oss}	V_{DD}=15 V, V_{GS}=0 V	-	3.8	5.1	
Reverse Diode						
Diode continous forward current	I_S	T_A=25 °C	-	-	2.5	A
Diode pulse current	$I_{S,pulse}$		-	-	29	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=2.5 A, T_j=25 °C	-	0.79	1	V
Reverse recovery charge	Q_{rr}	V_R=12 V, I_F=I_S, di_F/dt=400 A/µs	-	-	4	nC

[4)] See figure 16 for gate charge parameter definition


1 Power dissipation

$P_{tot}=f(T_A)$; $t_p \leq 10$ s



2 Drain current


$I_D=f(T_A)$; $V_{GS} \geq 10$ V; $t_p \leq 10$ s



3 Safe operating area

$I_D=f(V_{DS})$; $T_A=25$ °C[1)]; $D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJS}=f(t_p)$


parameter: $D=t_p/T$



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C


parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C


parameter: V_{GS}



7 Typ. transfer characteristics


I_D=f(V_{GS}); $|V_{DS}|>2|I_D|R_{DS(on)max}$

parameter: T_j




8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C



9 Drain-source on-state resistance


$R_{DS(on)}$=f(T_j); I_D=7.2 A; V_{GS}=10 V



10 Typ. gate threshold voltage


$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}

parameter: I_D



11 Typ. capacitances


C=f(V_{DS}); V_{GS}=0 V; f=1 MHz



12 Forward characteristics of reverse diode

I_F=f(V_{SD})


parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω


parameter: $T_{j(start)}$



14 Typ. gate charge


V_{GS}=f(Q_{gate}); I_D=3.6 A pulsed

parameter: V_{DD}




15 Drain-source breakdown voltage


$V_{BR(DSS)}$=f(T_j); I_D=1 mA



16 Gate charge waveforms



Package Outline **PG-DSO-8**



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	-	1.750	-	0.069
A1	0.100	-	0.004	-
A2	1.250	1.650	0.049	0.065
b	0.360	0.510	0.014	0.020
c	0.190	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
e	1.270		0.050	
N	8		8	
L	0.390	0.890	0.015	0.035
h	0.250	0.410	0.010	0.016
Θ	0°	8°	0°	8°
ccc	0.100		0.004	
ddd	0.200		0.008	
F1	5.590	5.790	0.220	0.228
F2	0.550	0.750	0.022	0.030
F3	1.210	1.410	0.048	0.056

REFERENCE
JEDEC / MS-012

SCALE
0 1.0 2mm

EUROPEAN PROJECTION

ISSUE DATE
19-09-2005

FILE
DSO-8_1

Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2006.
All Rights Reserved.

Attention please!
The information given in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.