Ordering number:EN1943A

PNP/NPN Epitaxial Planar Silicon Transistors

2SA1392/2SC3383

AF Amp Applications

Features


· Adoption of FBET process.
· AF amp.

Package Dimensions

unit:mm

2003A

[2SA1392/2SC3383]



JEDEC : TO-92
EIAJ : SC-43
SANYO : NF

B : Base
C : Collector
E : Emitter

( ) : 2SA1392

Specifications

Absolute Maximum Ratings at Ta = 25˚C

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V_{CBO}		(–)60	V
Collector-to-Emitter Voltage	V_{CEO}		(–)50	V
Emitter-to-Base Voltage	V_{EBO}		(–)6	V
Collector Current	I_C		(–)200	mA
Collector Current (Pulse)	I_{CP}		(–)400	mA
Collector Dissipation	P_C		400	mW
Junction Temperature	Tj		150	˚C
Storage Temperature	Tstg		–55 to +150	˚C


Electrical Characteristics at Ta = 25˚C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	I_{CBO}	V_{CB}=(–)40V, I_E=0			(–)0.1	μA
Emitter Cutoff Current	I_{EBO}	V_{EB}=(–)5V, I_C=0			(–)0.1	μA
DC Current Gain	$h_{FE}1$	V_{CE}=(–)6V, I_C=(–)1mA	100*		560*	
	$h_{FE}2$	V_{CE}=(–)6V, I_C=(–)0.1mA	70			
Gain-Bandwidth Product	f_T	V_{CE}=(–)6V, I_C=(–)10mA		250		MHz
				(200)		MHz
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=(–)100mA, I_B=(–)10mA			(–)0.3	V
Base-to-Emitter Saturation Voltage	$V_{BE(sat)}$	I_C=(–)100mA, I_B=(–)10mA			(–)1.0	V
Output Capacitance	C_{ob}	V_{CB}=(–)6V, f=1MHz		2.7		pF
				(3.7)		pF
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	I_C=(–)10μA, I_E=0	(–)60			V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C=(–)1mA, R_{BE}=∞	(–)50			V
Emitter-to-Base Breakdown Votage	$V_{(BR)EBO}$	I_E=(–)10μA, I_C=0	(–)6			V


* : The 2SA1392/2SC3383 are classified by 1mA h_{FE} as follows :


100	R	200	140	S	280	200	T	400	280	U	560


SANYO Electric Co.,Ltd. Semiconductor Bussiness Headquaters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN



IC - VCE
2SA1392
−70μA
−60μA
−50μA
−40μA
−30μA
−20μA
−10μA
IB=0
Collector Current, IC - mA
Collector to Emitter Voltage, VCE - V



IC - VCE
2SC3383
60μA
50μA
40μA
30μA
20μA
10μA
IB=0
Collector Current, IC - mA
Collector to Emitter Voltage, VCE - V



IC - VCE
2SA1392
−400μA
−350μA
−300μA
−250μA
−200μA
−150μA
−100μA
−50μA
IB=0
Collector Current, IC - mA
Collector to Emitter Voltage, VCE - V



IC - VCE
2SC3383
300μA
250μA
200μA
150μA
100μA
50μA
IB=0
Collector Current, IC - mA
Collector to Emitter Voltage, VCE - V



IC - VBE
2SA1392
VCE=−6V
Ta=25°C
Collector Current, IC - mA
Base to Emitter Voltage, VBE - V



IC - VBE
2SC3383
VCE=6V
Collector Current, IC - mA
Base to Emitter Voltage, VBE - mV



fT - IC
2SA1392
VCE=−6V
Gain-Bandwidth Product, fT - MHz
Collector Current, IC - mA



fT - IC
2SC3383
VCE=6V
Gain-Bandwidth Product, fT - MHz
Collector Current, IC - mA



hFE - IC
2SA1392
VCE=−6V
Ta=25°C
DC Current Gain, hFE
Collector Current, IC - mA



hFE - IC
2SC3383
VCE=6V
DC Current Gain, hFE
Collector Current, IC - mA



Cob - VCB
2SA1392
f=1MHz
Output Capacitance, Cob - pF
Collector to Base Voltage, VCB - V



Cob - VCB
2SC3383
f=1MHz
Output Capacitance, Cob - pF
Collector to Base Voltage, VCB - V



VCE(sat) - IC
2SA1392
hFE=10
Collector to Emitter Saturation Voltage, VCE(sat) - V
Collector Current, IC - mA


VCE(sat) - IC
2SC3383
hFE=10
Collector to Emitter Saturation Voltage, VCE(sat) - mV
Collector Current, IC - mA


VBE(sat) - IC
2SA1392
hFE=10
Base to Emitter Saturation Voltage, VBE(sat) - V
Collector Current, IC - mA


PC - Ta
2SA1392/2SC3383
Collector Dissipation, PC - mW
Ambient Temperature, Ta - °C





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:
① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
② Not impose any responsibilty for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1998. Specifications and information herein are subject to change without notice.