

MLS1000

Multimode Light Source



- 850 and 1300 nm LED source
- High stability output
- Temperature compensated
- Continuous and modulated outputs
- Exceptional battery life
- Ruggedised waterproof housing to IP54
- 3 Year manufacturers warranty
- Dry Cell or Rechargeable operation

DESCRIPTION

The MLS1000 is a stable optical dual LED source that can be used in conjunction with an optical power meter for optical loss testing of fiber optic cables. It has been designed to output 850nm or 1300nm at a level of -20 dBm into a 62.5/125 multi-mode fibre.

It is particularly suitable for the testing of LAN's, FDDI, and other multimode links whether inside or outside a building.

Although the MLS1000's main use is in multimode fiber optic cable loss testing, other applications include fiber continuity testing, connector testing, and patch lead testing.

Both CW (constant wave) and modulated outputs are available with LED mode indication.

Battery status warning provides battery condition indication. An optical charger is available when rechargeable batteries are fitted.

SPECIFICATION

Source Type:

Two LED's

Wavelength:

850nm & 1300nm typical

Wavelength Accuracy:

± 30nm

Output Level:

Typically >-20dBm into 62.5/125 multimode fiber

Output Stability:

Typically <0.1dB over 1hour at 23 Centigrade

Output:

Continuous or 1kHz Modulated

Batteries:

2 x AA Alkaline Cells
(NiMh on NiCad can be used)

Battery Life:

50 hours continuous
80 hours modulated

Power Input:

Can operate and charge internal batteries using optional charger

Optical Connector:

Supplied with ST connectors.

Safety:

Laser Class 1

Case Dimensions:

160 mm x 83 mm x 30 mm

Instrument Weight:

220g

Operational Temperature:

-15°C to +50°C (5°F to 122°F)

Operational Humidity:

95% at 40°C (104°F)

Storage Temperature:

-20°C to 70°C (-4°F to 158°F)

ORDERING INFORMATION

Item	Order Code	Item	Order Code
Multimode light source with ST connector	MLS1000	In-line gender changing adaptor with Multimode ST connectors	22440-019
Included Accessories		In-line gender changing adaptor with Single mode SC connectors	22440-020
User Guide	6172-626	In-line gender changing adaptor with Multimode SC connectors	22440-021
Test & Carry Pouch	6220-714	In-line gender changing adaptor with Single mode ST connectors	22440-022
Optional Accessories		In-line gender changing adaptor with Single mode FC connectors	22440-003
Single Mode Patch Cord with FC / SC Connectors (3 metres)	22440-007	Bare Fiber adaptor SC connector	25970-034
Single Mode Patch Cord with FC / FC Connectors (3 metres)	22440-008	Bare Fiber adaptor FC connector	25970-035
Single Mode Patch Cord with FC / ST Connectors (3 metres)	22440-009	Bare Fiber adaptor ST connector	25970-036
Single Mode Patch Cord with ST / ST Connectors (3 metres)	22440-015	Bare Fiber adaptor SC, ST and FC connectors	25970-037
Single mode patch cord with ST/SC connectors (3 metres)	22440-027	UK DC Power Supply	27900-050
Single Mode Patch Cord with SC / SC Connectors (3 metres)	22440-016	USA DC Power Supply	27900-051
Multimode Patch Cord with FC / FC Connectors (3 metres) 50 µm	22440-010	EU DC Power Supply	27900-052
Multimode Patch Cord with FC / ST Connectors (3 metres) 50µm	22440-011		
Multimode Patch Cord with FC / SC Connectors (3 metres) 50 µm	22440-012		
Multimode Patch Cord with ST / ST Connectors (3 metres) 50 µm	22440-013		
Multimode Patch Cord with ST / SC Connectors (3 metres) 50 µm	22440-014		
Multimode Patch Cord with SC / SC Connectors (3 metres) 50 µm	22440-017		
Multimode Patch Cord with FC / ST Connectors (3 metres) 62.5 µm	22440-028		
Multimode Patch Cord with ST / ST Connectors (3 metres) 62.5 µm	22440-029		
Multimode Patch Cord with ST / SC Connectors (3 metres) 62.5 µm	22440-030		
Multimode Patch Cord with FC / SC Connectors (3 metres) 62.5 µm	22440-031		
Multimode Patch Cord with SC / SC Connectors (3 metres) 62.5 µm	22440-032		
Multimode Patch Cord with FC / FC Connectors (3 metres) 62.5 µm	22440-033		

UK

Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342

UNITED STATES

4271 Bronze Way
Dallas TX 75237-1088 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399

OTHER TECHNICAL SALES OFFICES

Norristown USA, Toronto CANADA,
Mumbai INDIA, Trappes FRANCE,
Sydney AUSTRALIA and the
Kingdom of BAHRAIN.

Registered to ISO 9001:2000 Cert. no. Q 09290
Registered to ISO 14001-1996 Cert. no. EMS 61597

MLS1000_DS_en_V11

www.megger.com
Megger is a registered trademark